

In the Claims:

Please cancel claims 4 and 13, without prejudice, and amend claims 1, and

10. The status of the claims is as follows:

1. (Currently Amended) An optical storage apparatus for writing
| on and reading from a storage medium using a laser beam, comprising:

a light source for emitting a laser beam onto said storage medium;

a servo control unit for performing follow up control of said laser beam
onto said storage medium according to a reflected light from said storage medium;

an automatic power control (APC) detector for monitoring the emission
power of said light source; and

a control unit for calculating a drive instruction amount based on a detection
output of said APC detector, and performing automatic power control of said light source
according to said drive instruction amount, so that the emission power on said storage
medium is maintained to be a write power during said writing, and the emission power on
said storage medium is maintained to be a read power during said reading,

wherein said control unit measures an inclination of a relationship between
said drive instruction amount and the detection output of said APC detector, and judges
| the an abnormality of said APC detector by comparing a pre-measured inclination of the
relationship between said drive instruction amount and the detection output of said APC
detector with said measured inclination,

and wherein said ~~measured inclination and said pre-measured inclination are~~
| ~~obtained in a same drive instruction amount range~~ control unit judges the abnormality of

said APC detector by comparing a value obtained by dividing said measured inclination by said pre-measured inclination that is measured before a shipment of the optical storage apparatus with a threshold value.

2. (Original) The optical storage apparatus according to Claim 1, wherein said control unit measures the detection output of said APC detector when said light source is driven with said drive instruction amount, and measures the inclination of the relationship between said drive instruction amount and said detection output.

3. (Original) The optical storage apparatus according to Claim 1, wherein said control unit measures the inclination of the relationship between said drive instruction amount and the detection output of said APC detector when loading of said storage medium.

4. (Canceled)

5. (Withdrawn) The optical storage apparatus according to Claim 1, wherein said control unit performs said automatic power control with an arbitrary time interval, and measures the inclination of the relationship between said drive instruction amount and the detection output of said APC detector from said drive instruction amount at the start of said automatic power control.

6-9. (Cancelled)

10. (Currently Amended) An abnormality detection method of a detector for emission power control, comprising the steps of:

performing automatic power control of a light source which emits a laser beam for writing on and reading from a storage medium onto said storage medium according to a drive instruction amount calculated based on a detection output of an automatic power control (APC) detector for monitoring the emission power of said light source, so that the emission power on said storage medium is maintained to be a write power during said writing, and the emission power on said storage medium is maintained to be a read power during said reading;

measuring an inclination of a relationship between said drive instruction amount and the detection output of said APC detector; and

judging the abnormality of said APC detector by comparing a pre-measured inclination of the relationship between said drive instruction amount and said detection output of said APC detector with said measured inclination,

~~wherein said measured inclination and said pre-measured inclination are obtained in a same drive instruction amount range~~ judging comprises judging the abnormality of said APC detector by comparing a value obtained by dividing said measured inclination by said pre-measured inclination that is measured before a shipment of the optical storage apparatus with a threshold value.

11. (Original) The abnormality detection method of a detector for emission control according to Claim 10, wherein said measurement step comprises a step

of measuring the detection output of said APC detector when said light source is driven with said drive instruction amount, and a step of measuring the inclination of the relationship between said drive instruction amount and said detection output.

12. (Original) The abnormality detection method of a detector for emission control according to Claim 10, wherein said measuring step comprises a step of measuring the inclination of the relationship between said drive instruction amount and the detection output of said APC detector when said storage medium is loaded.

13. (Canceled)

14. (Withdrawn) The abnormality detection method of a detector for emission control according to Claim 10, wherein said measurement step comprises a step of performing said automatic power control with an arbitrary time interval, and a step of measuring the inclination of the relationship between said drive instruction amount and the detection output of said APC detector from said drive instruction amount at the start of said automatic power control.

15-18. (Cancelled)